SAFETY DATA SHEET

1. Identification

Product Identifier

Oatey Plumber's Putty

Other means of identification

Product code

1705E

Synonyms

Part Numbers: 31166, 31167, 31170, 31174, 48003, 48004

Recommended use

Plumbing Mastic

Recommended restrictions

Workers (and your customers or users in the case of resale) should be informed of the potential presence of respirable dust and respirable crystalline silica as well as their potential hazards. Appropriate training in the proper use and handling of this material should be provided as required under applicable regulations.

Manufacturer/Importer/Supplier/Distributor information

Company Name

Oatey Co.

Address

4700 West 160th St. Cleveland, OH 44135

Telephone

216-267-7100

E-mail

info@oatey.com

Transport Emergency

Chemtrec 1-800-424-9300 (Outside the US 1-703-527-3887)

Emergency First Aid Contact person

1-877-740-5015 MSDS Coordinator

2. Hazard(s) identification

Physical hazards

Not classified.

Health hazards

Not classified.

OSHA defined hazards

Not classified,

Label elements

Hazard symbol

None.

Signal word

None.

Hazard statement

The mixture does not meet the criteria for classification.

Precautionary statement

Prevention

Observe good industrial hygiene practices.

Response

Wash hands after handling.

Storage

Store away from incompatible materials.

Disposal

Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise

classified (HNOC)

Frequent or prolonged contact may defat and dry the skin, leading to discomfort and dermatitis.

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%	
Limestone	1317-65-3		
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	5-30	
Crystalline silica (Quartz)	14808-60-7	<1	
Other components below reportable levels		9,85	

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret,

4. First-aid measures

Inhalation

If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing.

Call a physician if symptoms develop or persist.

Skin contact

Rinse skin with water/shower. Get medical attention if irritation develops and persists.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. If ingestion of a large amount does occur, call a poison control center immediately.

Most important

Coughing.

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

General information

Treat symptomatically.

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Specific hazards arising from

the chemical Special protective equipment

and precautions for firefighters

Fire fighting equipment/instructions

Specific methods

General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Use water spray to cool unopened containers,

Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

For waste disposal, see section 13 of the SDS. Avoid discharge into drains, water courses or onto the ground.

Environmental precautions

7. Handling and storage

Precautions for safe handling

Keep formation of airborne dusts to a minimum. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid prolonged exposure.

Stop the flow of material, if this is without risk. Following product recovery, flush area with water.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Туре	Value	Form
Distillates (petroleum), hydrotreated heavy naphthenic (CAS	PEL.	5 mg/m3	Mist.
64742-52-5)		2000 mg/m3 500 ppm	
Limestone (CAS 1317-65-3)	PEL.	5 mg/m3 15 mg/m3	Respirable fraction. Total dust.

SDS US Oatev Plumber's Putty 2/7

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA .	0.3 mg/m3	Total dust.
(-) ,		0.1 mg/m3	Respirable.
US. ACGIH Threshold Limit Value	es		
Components	Туре	Value	Form
Crystalline silica (Quartz) CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
Distillates (petroleum), nydrotreated heavy naphthenic (CAS 34742-52-5)	TWA	5 mg/m3	Inhalable fraction.
US. NIOSH: Pocket Guide to Che	mical Hazards		

Components	Туре	Value	Form
Crystalline silica (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust,
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	Ceiling	1800 mg/m3	
,	STEL	10 mg/m3	Mist.
	TWA	5 mg/m3	Mist.
Limestone (CAS 1317-65-3)	TWA	5 mg/m3 10 mg/m3	Respirable. Total

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Occupational exposure to nulsance dust (total and respirable) and respirable crystalline silica

should be monitored and controlled.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection

Wear appropriate chemical resistant gloves.

Other

Wear suitable protective clothing.

Respiratory protection

Use a particulate filter respirator for particulate concentrations exceeding the Occupational

Exposure Limit.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective

equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical state

Solid.

Form

Putty. Off-white.

Color

Odor threshold

Slight.

Not available.

Odor

Not applicable

Melting point/freezing point

Not available.

Oatey Plumber's Putty

SDS US

Initial boiling point and boiling

range

Not determined

Flash point

> 212.0 °F (> 100.0 °C)

Evaporation rate

Not available.

Flammability (solid, gas)

Not available.

Upper/lower flammability or explosive limits

(%)

Flammability limit - lower

Not available.

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%)

Not available.

Explosive limit - upper (%)

Not available.

Vapor pressure

Not available.

Vapor density

Not available.

Relative density

1.87

Solubility(ies)

Solubility (water)

Not available.

Partition coefficient

Not available.

(n-octanol/water)

Auto-ignition temperature

Not available.

Decomposition temperature

Not available.

Viscosity

> 500000 cP

20 g/l

Other information

VOC (Weight %)

10. Stability and reactivity

Reactivity

The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability

Material is stable under normal conditions. No dangerous reaction known under conditions of normal use.

Possibility of hazardous

reactions

Contact with incompatible materials.

Conditions to avoid Incompatible materials

Acids, Fluorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation

Prolonged inhalation may be harmful.

Skin contact

No adverse effects due to skin contact are expected. Direct contact with eyes may cause temporary irritation.

Eye contact Ingestion

Expected to be a low ingestion hazard.

Symptoms related to the

Coughing.

physical, chemical and toxicological characteristics

Information on toxicological effects

Acute toxicity

Not available.

Skin corrosion/irritation

Prolonged skin contact may cause temporary irritation. Direct contact with eyes may cause temporary irritation.

Serious eye damage/eye irritation

Respiratory or skin sensitization

Respiratory sensitization

Not a respiratory sensitizer.

Skin sensitization

This product is not expected to cause skin sensitization.

Oatey Plumber's Putty

SDS US

Issue date: 22-April-2015 Revision date: -925325 Version #: 01

Germ cell mutagenicity

No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity

In 1997, IARC (the International Agency for Research on Cancer) concluded that crystalline silica inhaled from occupational sources can cause lung cancer in humans. However in making the overall evaluation. IARC noted that "carcinogenicity was not detected in all industrial circumstances studied. Carcinogenicity may be dependent on inherent characteristics of the crystalline silica or on external factors affecting its biological activity or distribution of its polymorphs." (IARC Monographs on the evaluation of the carcinogenic risks of chemicals to

humans, Silica, silicates dust and organic fibres, 1997, Vol. 68, IARC, Lyon, France.) Risk of cancer cannot be excluded with prolonged exposure.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline silica (Quartz) (CAS 14808-60-7)

1 Carcinogenic to humans.

Distillates (petroleum), hydrotreated heavy naphthenic

3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-52-5)

NTP Report on Carcinogens

Crystalline silica (Quartz) (CAS 14808-60-7)

Known To Be Human Carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910,1001-1050)

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Aspiration hazard

Not an aspiration hazard.

Chronic effects

Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

Further information

This product has no known adverse effect on human health.

No data is available on the degradability of this product.

12. Ecological information

Ecotoxicity

The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment,

Persistence and degradability

Bioaccumulative potential

Mobility in soil

No data available.

Other adverse effects

No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions

Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and Not applicable.

the IBC Code

Oatey Plumber's Putty 925325 Version #: 01

Revision date: -

Issue date: 22-April-2015

SDS US

5/7

15. Regulatory information

US federal regulations

This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard

Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories

Immediate Hazard - No Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Nο

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Crystalline silica (Quartz) (CAS 14808-60-7)

Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)

Limestone (CAS 1317-65-3)

US, New Jersey Worker and Community Right-to-Know Act

Crystalline silica (Quartz) (CAS 14808-60-7)

Limestone (CAS 1317-65-3)

US. Pennsylvania Worker and Community Right-to-Know Law

Crystalline silica (Quartz) (CAS 14808-60-7)

Limestone (CAS 1317-65-3)

US. Rhode Island RTK

Not regulated.

US. California Proposition 65

WARNING: This product contains a chemical known to the State of California to cause cancer and birth defects or other reproductive harm.

US - California Proposition 65 - Carcinogens & Reproductive Toxicity (CRT): Listed substance

Crystalline silica (Quartz) (CAS 14808-60-7)

Methanol (CAS 67-56-1)

International Inventories

Country(s) or region Inventory name On inventory (yes/no)*

Toxic Substances Control Act (TSCA) Inventory United States & Puerto Rico

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s). A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing

16. Other information, including date of preparation or last revision

Issue date

22-April-2015

SDS US Oatev Plumber's Putty

Yes

Revision date

Version#

01

HMIS® ratings

Health: 0 Flammability: 0 Physical hazard: 0

NFPA ratings



Disclaimer

Oatey Co. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.

Oatey Plumber's Putty

SDS US

925325 Version #: 01 Revision date: - Issue date: 22-April-2015

	·	•			
					•
				J	
					1
				•	
					•
•					
•					