ORC WORLD WIDE

SAFETY DATA SHEET

1. Identification

Product identifier ZRC Cold Galvanizing Compound

Other means of identification

Product number 10001 - 10004

Recommended use Corrosion protection of iron and steel.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Supplier/Manufacturer ZRC Worldwide

Address 145 Enterprise Drive, Marshfield, MA 02050

Telephone 781-319-0400

Emergency telephone

(CHEMTREC)

703-527-3887 CCN15781

Email info@zrcworldwide.com

2. Hazard(s) identification

Physical hazardsFlammable liquidsCategory 3Health hazardsSkin corrosion/irritationCategory 2CarcinogenicityCategory 2

Specific target organ toxicity, repeated Category 1 (central nervous system)

exposure

Environmental hazards Hazardous to the aquatic environment, acute Category 1

hazard

Hazardous to the aquatic environment, Category 1

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor. Causes skin irritation. Suspected of causing cancer. Causes

damage to organs (central nervous system) through prolonged or repeated exposure. Very toxic

to aquatic life with long lasting effects.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Do not breathe mist/vapors. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection. Observe good industrial

hygiene practices.

Response If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse. If exposed or concerned: Get medical advice/attention. In case of fire: Use water fog, foam, dry

chemical powder, dry sand, carbon dioxide to extinguish. Collect spillage.

Storage Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

ZRC Cold Galvanizing Compound SDS US 917537 Version #: 07 Revision date: 28-February-2020 Issue date: 14-December-2013 1 / 10

None known.

Supplemental information

None.

3. Composition/information on ingredients

Mixtures

CAS number	%	
7440-66-6	75 - 85	
64742-88-7	4 - 6	
64742-47-8	4 - 5	
1314-13-2	2 - 3	
100-41-4	0.1 - 1	
111-84-2	0.1 - 1	
	7440-66-6 64742-88-7 64742-47-8 1314-13-2 100-41-4	

Composition comments

All concentrations are in percent by weight unless otherwise indicated. Components not listed are either non-health-hazardous or are below reportable limits.

4. First-aid measures

Inhalation Skin contact Move to fresh air. Call a physician if symptoms develop or persist.

Take off immediately all contaminated clothing. Rinse skin with water/shower. If skin irritation

Eye contact

occurs: Get medical advice/attention. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delaved

Indication of immediate medical attention and special treatment needed

General information

Narcosis. Behavioral changes. Decrease in motor functions. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim under observation. Symptoms may be delayed.

Take off all contaminated clothing immediately. IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing

media

Specific hazards arising from

Special protective equipment

the chemical

and precautions for firefighters

Fire fighting

equipment/instructions Specific methods

General fire hazards

Water fog. Foam. Dry chemical powder. Dry sand. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source of ignition and flash back. During fire, gases hazardous to health may be formed.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do so without risk. Cool containers exposed to flames with water until well after the fire is out.

Use standard firefighting procedures and consider the hazards of other involved materials.

Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist/vapors. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

2 / 10 917537 Version #: 07 Revision date: 28-February-2020 Issue date: 14-December-2013

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Take precautionary measures against static discharge. Use only non-sparking tools.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Following product recovery, flush area with water.

Small Spills: Absorb with earth, sand or other non-combustible material and transfer to containers for later disposal. Wipe up with absorbent material. Clean surface thoroughly to remove residual contamination.

Environmental precautions

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle, store or open near an open flame, sources of heat or sources of ignition. Protect material from direct sunlight. Explosion-proof general and local exhaust ventilation. Take precautionary measures against static discharges. Use non-sparking tools and explosion-proof equipment. Do not breathe mist/vapors. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep away from heat, sparks and open flame. Prevent electrostatic charge build-up by using common bonding and grounding techniques. Store in a cool, dry place out of direct sunlight. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep in an area equipped with sprinklers. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air	Contaminants (29 CFR 1910.1000)		
Components	Туре	Value	Form
Ethylbenzene (CAS 100-41-4)	PEL	435 mg/m3	
		100 ppm	
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	PEL	400 mg/m3	
		100 ppm	
Zinc oxide (CAS 1314-13-2)	PEL	5 mg/m3	Respirable fraction.
		5 mg/m3	Fume.
		15 mg/m3	Total dust.
US. ACGIH Threshold Limit Values	3		
Components	Туре	Value	Form
Ethylbenzene (CAS 100-41-4)	TWA	20 ppm	
Nonane (CAS 111-84-2)	TWA	200 ppm	
Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)	TWA	200 mg/m3	Non-aerosol.
Zinc oxide (CAS 1314-13-2)	STEL	10 mg/m3	Respirable fraction.
	TWA	2 mg/m3	Respirable fraction.

SDS US

917537 Version #: 07 Revision date: 28-February-2020 Issue date: 14-December-2013 3 / 10

Components	Туре	Value	Form
Ethylbenzene (CAS 100-41-4)	STEL	545 mg/m3	
		125 ppm	
	TWA	435 mg/m3	
		100 ppm	
Nonane (CAS 111-84-2)	TWA	1050 mg/m3	
		200 ppm	
Zinc oxide (CAS 1314-13-2)	Ceiling	15 mg/m3	Dust.
	STEL	10 mg/m3	Fume.
	TWA	5 mg/m3	Dust.
		5 mg/m3	Fume.

Biological limit values

ACGIH Biological	Exposure Indices
Components	Value

Components	Value	Determinant	Specimen	Sampling Time	
Ethylbenzene (CAS 100-41-4)	0.15 g/g	Sum of mandelic acid and phenylglyoxylic acid	Creatinine in urine	*	

^{* -} For sampling details, please see the source document.

Exposure guidelines

US ACGIH Threshold Limit Values: Skin designation

Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

Can be absorbed through the skin.

Appropriate engineering

controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. Provide easy access to water supply or an emergency shower.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles). Wear face shield if there is risk of splashes.

Skin protection

Hand protection Wear appropriate chemical resistant gloves. Be aware that the liquid may penetrate the gloves.

Frequent change is advisable. Nitrile or neoprene gloves are recommended. Other suitable gloves

can be recommended by the glove supplier.

Skin protection

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Check with respiratory protective

equipment suppliers.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Always observe good personal hygiene measures, such as washing after handling the material and before eating,

drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

9. Physical and chemical properties

Appearance

Physical stateLiquid.FormLiquid.ColorGray.

Odor Hydrocarbon.
Odor threshold Not available.

ZRC Cold Galvanizing Compound SDS US

pH Not available.Melting point/freezing point Not available.Initial boiling point and boiling Not available.

range

Flash point 111.2 °F (44.0 °C) Setaflash
Evaporation rate <1 (n-Butyl acetate=1)

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

0.9 %

(%)

Flammability limit - upper 7 %

(%)

 Vapor pressure
 0.8 kPa (25°C / 77°F)

 Vapor density
 > 1 (Air=1) (25°C / 77°F)

Relative density 2.88 (H2O=1)

Solubility(ies)

Solubility (water) Slightly soluble in water.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature Not available.

Decomposition temperature Not available.

Viscosity 1800 mPa·s (25°C / 77°F)

Other information

Bulk density24 lb/galExplosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.VOC385 g/l

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Protect against direct sunlight. Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition Decomposition is not expected under normal conditions of use and storage. Fire or high

products temperatures create: Carbon oxides. Fumes of metal oxides.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

Narcosis. Behavioral changes. Decrease in motor functions. Direct contact with eyes may cause temporary irritation. Skin irritation. May cause redness and pain. Prolonged exposure may cause

chronic effects.

Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

ZRC Cold Galvanizing Compound SDS US 917537 Version #: 07 Revision date: 28-February-2020 Issue date: 14-December-2013 5 / 10

Components **Species Test Results**

Ethylbenzene (CAS 100-41-4)

Acute

Dermal

LD50 Rabbit 15400 mg/kg

Inhalation

LC50 Rat 17.4 mg/l, 4 hours

Oral

LD50 Rat 3500 - 4700 mg/kg

Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Oral

Rat LD50 > 5000 mg/kg

Zinc (CAS 7440-66-6)

Acute Oral

LD50 Mouse > 5 g/kg

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Direct contact with eyes may cause temporary irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Not classified. However: The product contains a small amount of sensitizing substance which may Skin sensitization

provoke an allergic reaction among sensitive individuals.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Ethylbenzene (CAS 100-41-4) 2B Possibly carcinogenic to humans.

Solvent naphtha (petroleum), medium aliph. 3 Not classifiable as to carcinogenicity to humans.

(CAS 64742-88-7)

NTP Report on Carcinogens

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Causes damage to organs (central nervous system) through prolonged or repeated exposure.

Aspiration hazard Not an aspiration hazard.

Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated **Chronic effects**

exposure. Prolonged exposure may cause chronic effects.

Further information Symptoms may be delayed.

12. Ecological information

Ecotoxicity Very toxic to aquatic life with long lasting effects.

SDS US 917537 Version #: 07 Revision date: 28-February-2020 Issue date: 14-December-2013

Test Results Components **Species**

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Aquatic

Fish LC50 Rainbow trout.donaldson trout 2.9 mg/l, 96 hours

(Oncorhynchus mykiss)

Ethylbenzene (CAS 100-41-4)

Aquatic Acute

Water flea (Daphnia magna) Crustacea EC50 1.81 - 2.38 mg/l, 48 hours

LC50 Fish Rainbow trout, donaldson trout 4.2 mg/l, 96 hours

(Oncorhynchus mykiss)

Chronic

EC50 Ceriodaphnia dubia 3.6 mg/l, 7 days Crustacea

Zinc (CAS 7440-66-6)

Aquatic

Acute

Crustacea EC50 Daphnia magna 0.07 mg/l LC50 Fish Oncorhynchus mykiss 0.14 mg/l

Zinc oxide (CAS 1314-13-2)

Aquatic

LC50 Crustacea Water flea (Daphnia magna) 0.098 mg/l, 48 Hours

Persistence and degradability

The product contains inorganic compounds which are not biodegradable.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

Ethylbenzene (CAS 100-41-4) 3.15

Mobility in soil The product is slightly soluble in water. Expected to be slightly to moderately mobile in soil.

The product contains volatile organic compounds which have a photochemical ozone creation Other adverse effects

potential. This product contains one or more substances identified as hazardous air pollutants

(HAPs) per the US Federal Clean Air Act (see section 15).

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Incinerate the

material under controlled conditions in an approved incinerator. Do not incinerate sealed containers. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in

accordance with local/regional/national/international regulations.

Local disposal regulations

Hazardous waste code

Dispose in accordance with all applicable regulations. D001: Waste Flammable material with a flash point <140 F

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner.

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

UN1263 **UN number** UN proper shipping name

Transport hazard class(es)

Paint

Class 3 Subsidiary risk 3 Label(s) Ш Packing group

Environmental hazards

Marine pollutant Yes

917537 Version #: 07 Revision date: 28-February-2020

ZRC Cold Galvanizing Compound

Issue date: 14-December-2013

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

UN1263 **UN** number **UN** proper shipping name Paint

Transport hazard class(es)

Class 3 Subsidiary risk 3 Label(s) Ш **Packing group** Yes **Environmental hazards**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

UN number UN1263 **UN proper shipping name** Paint

Transport hazard class(es) Class 3 Subsidiary risk Ш Packing group **Environmental hazards**

Marine pollutant Yes F-E. S-E **EmS**

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Transport in bulk according to

Annex II of MARPOL 73/78 and

the IBC Code

15. Regulatory information

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication US federal regulations

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not applicable.

Nonane (CAS 111-84-2) 1.0 % One-Time Export Notification only.

CERCLA Hazardous Substance List (40 CFR 302.4)

Listed. Ethylbenzene (CAS 100-41-4) Nonane (CAS 111-84-2) Listed. Zinc (CAS 7440-66-6) Listed. Zinc oxide (CAS 1314-13-2) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

Toxic Substances Control Act (TSCA) All components of the mixture on the TSCA 8(b) inventory are designated

"active".

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous Yes

chemical

Classified hazard Flammable (gases, aerosols, liquids, or solids)

Skin corrosion or irritation categories

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Ethylbenzene	100-41-4	0.1 - 1	
Zinc	7440-66-6	75 - 85	
Zinc oxide	1314-13-2	2 - 3	

ZRC Cold Galvanizing Compound SDS US Issue date: 14-December-2013

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Ethylbenzene (CAS 100-41-4)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

US state regulations

US. Massachusetts RTK - Substance List

Ethylbenzene (CAS 100-41-4) Nonane (CAS 111-84-2) Zinc (CAS 7440-66-6) Zinc oxide (CAS 1314-13-2)

US. New Jersey Worker and Community Right-to-Know Act

Distillates (petroleum), hydrotreated light (CAS 64742-47-8)

Ethylbenzene (CAS 100-41-4) Nonane (CAS 111-84-2)

Solvent naphtha (petroleum), medium aliph. (CAS 64742-88-7)

Zinc (CAS 7440-66-6) Zinc oxide (CAS 1314-13-2)

US. Pennsylvania Worker and Community Right-to-Know Law

Ethylbenzene (CAS 100-41-4) Nonane (CAS 111-84-2) Zinc (CAS 7440-66-6) Zinc oxide (CAS 1314-13-2)

US. Rhode Island RTK

Ethylbenzene (CAS 100-41-4) Nonane (CAS 111-84-2) Zinc (CAS 7440-66-6) Zinc oxide (CAS 1314-13-2)

California Proposition 65



WARNING: This product can expose you to Ethylbenzene, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Ethylbenzene (CAS 100-41-4) Listed: June 11, 2004

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Ethylbenzene (CAS 100-41-4) Zinc (CAS 7440-66-6)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No
Taiwan	Taiwan Chemical Substance Inventory (TCSI)	Yes

917537 Version #: 07 Revision date: 28-February-2020 Issue date: 14-December-2013 9 / 10

Country(s) or region Inventory name On inventory (yes/no)*

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

*A "Yes" indicates this product complies with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information, including date of preparation or last revision

Issue date 14-December-2013
Revision date 28-February-2020

Version # 07

NFPA ratings



Disclaimer

This information is provided without warranty. The information is believed to be correct. This information should be used to make an independent determination of the methods to safeguard workers and the environment.

ZRC Cold Galvanizing Compound SDS US