



SI-PZ1043 Flush

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Date of issue: 12/18/2014

Revision date: 01/01/2021

Version: 1.4

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Name : SI-PZ1043 Flush
Product code : SI-PZ1043
Synonyms : SI-PZ1043-Q, SI-PZ1043-T, SI-PZ1043-G, SI-PZ1043-P, SI-PZ1043-500C, SI-PZ1043-200C, SI-PZ1043-500, SI-PZ1043-500X,, SI-PZ1043-350

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Flush for printing processes

1.3. Details of the supplier of the safety data sheet

Squid Ink Manufacturing, Inc.
1173 Osborne Road
Spring Lake Park, MN 55432
United States of America

phone: 763-795-8856
fax: 763-795-8867
email: kschneider@squidink.com

1.4. Emergency telephone number

24hr Emergency number : +1 800-424-9300 - Chemtrec

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS-US classification

Asp. Tox. 1 H304 - May be fatal if swallowed and enters airways
Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labeling

Hazard pictograms (GHS-US) :



GHS08

Signal word (GHS-US) : Danger
Hazard statements (GHS-US) : H304 - May be fatal if swallowed and enters airways
Precautionary statements (GHS-US) : P301+P310 - If swallowed: Immediately call a doctor
P331 - Do NOT induce vomiting
P405 - Store locked up
P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

SI-PZ1043 Flush

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS-US classification
white mineral oil (petroleum)	(CAS No) 8042-47-5	>= 50	Asp. Tox. 1, H304
glycerol	(CAS No) 56-81-5	1-20	Not classified

Full text of H-phrases: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
- First-aid measures after skin contact : Wash skin with plenty of water.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Immediately call a poison center or doctor/physician. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

- Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. Risk of lung edema.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Reactivity : The product is non-reactive under normal conditions of use, storage and transport.

5.3. Advice for firefighters

- Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

- Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

- Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

- Methods for cleaning up : Take up liquid spill into absorbent material.
- Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
- Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

- Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

SI-PZ1043 Flush

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

white mineral oil (petroleum) (8042-47-5)		
ACGIH	ACGIH TWA (mg/m³)	5 mg/m³ (Mineral oil, pure, highly and severely refined; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value; Inhalable fraction)
glycerol (56-81-5)		
ACGIH	Remark (ACGIH)	URT irr

8.2. Exposure controls

- Appropriate engineering controls : Ensure good ventilation of the work station. Provide adequate general and local exhaust ventilation.
- Personal protective equipment : Protective clothing. Protective goggles. Gloves.



- Hand protection : Protective gloves.
- Eye protection : Where eye contact may occur from use, Wear eye protection.
- Skin and body protection : Wear suitable protective clothing.
- Respiratory protection : Where exposure through inhalation may occur from use, respiratory protection equipment is recommended.
- Environmental exposure controls : Avoid release to the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

- Physical state : Liquid
- Color : clear amber
- Odor : Slight
- Odor threshold : No data available
- pH : No data available
- Melting point : Not applicable
- Freezing point : No data available
- Boiling point : > 200 °F
- Flash point : > 200 °F
- Relative evaporation rate (butyl acetate=1) : No data available
- Flammability (solid, gas) : No data available
- Explosion limits : No data available
- Explosive properties : No data available
- Oxidizing properties : No data available
- Vapor pressure : No data available
- Relative density : No data available
- Relative vapor density at 20 °C : No data available
- Solubility : Water: Solubility in water of component(s) of the mixture :
• : insoluble • glycerol: 100 g/100ml (25 °C, Complete)
- Log Pow : No data available
- Auto-ignition temperature : No data available
- Decomposition temperature : No data available
- Viscosity : No data available
- Viscosity, kinematic : No data available
- Viscosity, dynamic : No data available

9.2. Other information

No additional information available

SI-PZ1043 Flush

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Not classified
(Based on available data, the classification criteria are not met)

white mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg body weight (Rat; Equivalent or similar to OECD 401; Experimental value)
LD50 dermal rabbit	> 2000 mg/kg body weight (Rabbit; Experimental value; Equivalent or similar to OECD 402)
LC50 inhalation rat (mg/l)	> 5 mg/l/4h (Rat; Experimental value)
glycerol (56-81-5)	
LD50 oral rat	27200 mg/kg (Rat; Experimental value)
LC50 inhalation rat (mg/l)	> 2,75 mg/l/4h (Rat; Experimental value)
ATE US (oral)	27200,000 mg/kg body weight

Skin corrosion/irritation : Not classified
(Based on available data, the classification criteria are not met)

Serious eye damage/irritation : Not classified
(Based on available data, the classification criteria are not met)

Respiratory or skin sensitization : Not classified
(Based on available data, the classification criteria are not met)

Germ cell mutagenicity : Not classified
(Based on available data, the classification criteria are not met)

Carcinogenicity : Not classified
(Based on available data, the classification criteria are not met)

white mineral oil (petroleum) (8042-47-5)	
IARC group	3 - Not classifiable

Reproductive toxicity : Not classified
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (single exposure) : Not classified
(Based on available data, the classification criteria are not met)

Specific target organ toxicity (repeated exposure) : Not classified
(Based on available data, the classification criteria are not met)

Aspiration hazard : May be fatal if swallowed and enters airways.
(Based on available data, the classification criteria are not met)

Symptoms/injuries after ingestion : May be fatal if swallowed and enters airways. Risk of lung edema.

SI-PZ1043 Flush

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.

white mineral oil (petroleum) (8042-47-5)	
LC50 fish 1	> 100 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Oncorhynchus mykiss; Static system; Fresh water; Experimental value)
EC50 Daphnia 1	> 100 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 1	>= 100 mg/l (NOEL; OECD 201: Alga, Growth Inhibition Test; 72 h; Pseudokirchneriella subcapitata; Static system; Fresh water; Weight of evidence)

glycerol (56-81-5)	
LC50 fish 1	54000 mg/l (LC50; 96 h; Salmo gairdneri; Static system; Fresh water)
EC50 Daphnia 1	> 10000 mg/l (EC50; 24 h; Daphnia magna; Static system; Fresh water)
Threshold limit algae 1	> 10000 mg/l (EC0; 8 days; Scenedesmus quadricauda; Static system; Fresh water)

12.2. Persistence and degradability

white mineral oil (petroleum) (8042-47-5)	
Persistence and degradability	Not readily biodegradable in water. Adsorbs into the soil.
glycerol (56-81-5)	
Persistence and degradability	Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0,87 g O ₂ /g substance
Chemical oxygen demand (COD)	1,16 g O ₂ /g substance
ThOD	1,217 g O ₂ /g substance
BOD (% of ThOD)	0,71

12.3. Bioaccumulative potential

white mineral oil (petroleum) (8042-47-5)	
Log Pow	> 6 (Calculated)
Bioaccumulative potential	High potential for bioaccumulation (Log Kow > 5).
glycerol (56-81-5)	
Log Pow	-1,75 (Experimental value; Equivalent or similar to OECD 107)
Bioaccumulative potential	Bioaccumulation: Not applicable.

12.4. Mobility in soil

glycerol (56-81-5)	
Surface tension	0,0634 N/m (20 °C; 1000 g/l)

12.5. Other adverse effects

Effect on the global warming : No known ecological damage caused by this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
Ecology - waste materials : Avoid release to the environment.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT
Not dangerous goods in terms of transport regulations

TDG

Not dangerous goods in terms of transport regulations

Transport by sea

Not dangerous goods in terms of transport regulations

SI-PZ1043 Flush

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Air transport

Not dangerous goods in terms of transport regulations

SECTION 15: Regulatory information

15.1. US Federal regulations

white mineral oil (petroleum) (8042-47-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

glycerol (56-81-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

15.2. International regulations

CANADA

No additional information available

EU-Regulations

No additional information available

National regulations

No additional information available

15.3. US State regulations

No additional information available

SECTION 16: Other information

Revision date : 01/01/2021


Full text of H-phrases:

Asp. Tox. 1	Aspiration hazard Category 1
H304	May be fatal if swallowed and enters airways

NFPA health hazard : 0 - Exposure under fire conditions would offer no hazard beyond that of ordinary combustible materials.

NFPA fire hazard : 1 - Must be preheated before ignition can occur.

NFPA reactivity : 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health : 0 Minimal Hazard - No significant risk to health

Flammability : 1 Slight Hazard - Materials that must be preheated before ignition will occur. Includes liquids, solids and semi solids having a flash point above 200 F. (Class IIIB)

Physical : 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection : C

C - Safety glasses, Gloves, Synthetic apron

SDS US (GHS HazCom 2012)

Disclaimer: This information contained is furnished without warranty of any kind, and is herein given in good faith. No warranty, expressed or implied, is made. Squid Ink Manufacturing, Inc. assumes no responsibility for personal injury or property damage to vendors, users, or third parties. While the information is believed to be reliable, we do not guarantee its accuracy. Purchasers are encouraged to make their own tests with materials described herein and must make independent determination of suitability and completeness of information from all sources to assure proper use with materials and compatibility with equipment.