

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Material name : MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Material number : 000000000001003241

Manufacturer or supplier's details

Company : Zep Inc.

Address : 350 Joe Frank Harris Parkway, SE
Emerson, GA 30137

Telephone : Compliance Services - 877-428-9937

Emergency telephone numbers

For SDS Information : Compliance Services - 877-428-9937

For a Medical Emergency : 877-541-2016 Toll Free - All Calls Recorded

For a Transportation
Emergency : CHEMTREC: 800-424-9300 - All Calls Recorded.
In the District of Columbia 202-483-7616

Recommended use of the chemical and restrictions on use

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Appearance	gel
Colour	metallic, silver
Odour	oily

GHS Classification

Germ cell mutagenicity : Category 1B

Reproductive toxicity : Category 2

GHS label elements

Hazard pictograms :



Health hazard

Signal word : Danger

Hazard statements : H340 May cause genetic defects.
H361 Suspected of damaging fertility or the unborn child.

Precautionary statements : **Prevention:**
P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.
Response:

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

P308 + P313 IF exposed or concerned: Get medical advice/attention.

Storage:

P405 Store locked up.

Disposal:

P501 Dispose of contents/container in accordance with local regulation.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Concentration [%]
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	>= 20 - < 30
Distillates (petroleum), hydrotreated light paraffinic	64742-55-8	>= 20 - < 30
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	>= 20 - < 30
Distillates (petroleum), hydrotreated light naphthenic	64742-53-6	>= 10 - < 20
graphite	7782-42-5	>= 5 - < 10
Silicon, amorphous	112945-52-5	>= 3 - < 5
aluminium	7429-90-5	>= 1 - < 3
Stoddard solvent	8052-41-3	>= 1 - < 3
quartz (SiO ₂)	14808-60-7	>= 0.1 - < 1

The exact percentages of disclosed substances are withheld as trade secrets.

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Wash off with soap and water.
If skin irritation persists, call a physician.
If on skin, rinse well with water.
If on clothes, remove clothes.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.
Protect unharmed eye.
Keep eye wide open while rinsing.
If eye irritation persists, consult a specialist.
- If swallowed : Induce vomiting immediately and call a physician.

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

Keep respiratory tract clear.
Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.
Take victim immediately to hospital.

Most important symptoms and effects, both acute and delayed : Effects may be delayed, symptoms may include minor eye or skin irritation.
Overexposure may cause mild eye or skin irritation.

Notes to physician : Treat symptomatically. Symptoms may be delayed.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : Carbon dioxide (CO₂)
Carbon monoxide
Smoke

Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Further information : Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains, inform respective authorities.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : Do not breathe vapours/dust.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
For personal protection see section 8.
Smoking, eating and drinking should be prohibited in the application area.
Dispose of rinse water in accordance with local and national regulations.
- Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated place.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Observe label precautions.
Electrical installations / working materials must comply with the technological safety standards.
- Materials to avoid : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
		PEL	100 ppm 525 mg/m3	CAL PEL
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	TWA (Mist)	5 mg/m3	OSHA Z-1
		TWA (Inhalable fraction)	5 mg/m3	ACGIH
graphite	7782-42-5	TWA (Respirable)	2.5 mg/m3	NIOSH REL
		TWA (Dust)	15 Million particles per cubic foot	OSHA Z-3
Silicon, amorphous	112945-52-5	TWA (Dust)	20 Million particles per cubic foot	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2	OSHA Z-3
		TWA	6 mg/m3	NIOSH REL
aluminium	7429-90-5	TWA	5 mg/m3	NIOSH REL

SAFETY DATA SHEET**MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T**

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

		(Respirable)		
		TWA (total)	10 mg/m3	NIOSH REL
		TWA (total dust)	15 mg/m3	OSHA Z-1
		TWA (respirable fraction)	5 mg/m3	OSHA Z-1
		TWA (Total dust)	15 mg/m3	OSHA P0
		TWA (respirable dust fraction)	5 mg/m3	OSHA P0
		TWA (Respirable fraction)	1 mg/m3	ACGIH
Stoddard solvent	8052-41-3	TWA	100 ppm	ACGIH
		TWA	350 mg/m3	NIOSH REL
		C	1,800 mg/m3	NIOSH REL
		TWA	500 ppm 2,900 mg/m3	OSHA Z-1
		TWA	100 ppm 525 mg/m3	OSHA P0
		PEL	100 ppm 525 mg/m3	CAL PEL
quartz (SiO2)	14808-60-7	TWA (total dust)	30 mg/m3 / %SiO2+2	OSHA Z-3
		TWA (Respirable dust)	0.05 mg/m3	NIOSH REL
		TWA (Respirable dust)	0.05 mg/m3	OSHA Z-1
		PEL (Respirable dust)	0.05 mg/m3	CAL PEL

Engineering measures : effective ventilation in all processing areas

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Hand protection

Material : Protective gloves
Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection

: Access to clean water to rinse eyes must be available, options include: eye wash stations or showers, or eye wash bottles with pure water.
Tightly fitting safety goggles

Skin and body protection

: Impervious clothing

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

Choose body protection according to the amount and concentration of the dangerous substance at the work place.

Hygiene measures : When using do not eat or drink.
When using do not smoke.
Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: gel
Colour	: metallic, silver
Odour	: oily
Odour Threshold	: not determined
pH	: Not applicable
Melting point/freezing point	: Not applicable
Boiling point	: No data available
Flash point	: > 204.4 ° C Method: Cleveland open cup
Evaporation rate	: Not applicable
Upper explosion limit	: not determined
Lower explosion limit	: not determined
Vapour pressure	: < 0.01 hPa
Density	: 0.8 g/cm ³
Solubility(ies)	
Water solubility	: negligible
Solubility in other solvents	: not determined
Viscosity	
Viscosity, kinematic	: > 10000 mm ² /s (40 ° C)

SECTION 10. STABILITY AND REACTIVITY

Reactivity	: Stable
Chemical stability	: Stable under normal conditions.

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

Possibility of hazardous reactions	: No decomposition if stored and applied as directed.
Conditions to avoid	: No data available
Incompatible materials	: Oxidizing agents
Hazardous decomposition products	: Carbon oxides Organic Substances

SECTION 11. TOXICOLOGICAL INFORMATION

Potential Health Effects

Aggravated Medical Condition	: None known.
Symptoms of Overexposure	: Effects may be delayed, symptoms may include minor eye or skin irritation. Overexposure may cause mild eye or skin irritation. Treat symptomatically. Symptoms may be delayed.

Carcinogenicity:

IARC	No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC. Group 1: Carcinogenic to humans
ACGIH	quartz (SiO ₂) 14808-60-7 Confirmed animal carcinogen with unknown relevance to humans Solvent naphtha (petroleum), light arom. 64742-95-6
OSHA	No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.
NTP	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

Acute toxicity

Product:

Acute oral toxicity	: Acute toxicity estimate : > 5,000 mg/kg Method: Calculation method
---------------------	---

Components:

Distillates (petroleum), hydrotreated heavy naphthenic:

Acute oral toxicity	: LD50 Rat: > 5,000 mg/kg
---------------------	---------------------------

Acute inhalation toxicity	: LC50 Rat: > 5 mg/l Exposure time: 4 h
---------------------------	--

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

Acute dermal toxicity : LD50 Rabbit: > 5,000 mg/kg

Silicon, amorphous:

Acute oral toxicity : LD50 Oral Rat: 3,160 mg/kg

aluminium:

Acute oral toxicity : LD50 Rat: > 15,900 mg/kg

Acute inhalation toxicity : LC50 Rat: > 0.888 mg/l
Exposure time: 4 h

Skin corrosion/irritation

Product:

Remarks: May cause skin irritation and/or dermatitis.

Serious eye damage/eye irritation

Product:

Remarks: Vapours may cause irritation to the eyes, respiratory system and the skin.

Respiratory or skin sensitisation

No data available

Germ cell mutagenicity

No data available

Carcinogenicity

Product:

Carcinogenicity - Assessment : Not classifiable as a human carcinogen., Not classified due to product form (grease or paste) and classification route of entry (inhaled powder).

Reproductive toxicity

No data available

STOT - single exposure

No data available

STOT - repeated exposure

No data available

Aspiration toxicity

No data available

Further information

Product:

Remarks: No data available

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

No data available

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Regulation

40 CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602 Class I Substances

Remarks

This product neither contains, nor was manufactured with a Class I or Class II ODS as defined by the U.S. Clean Air Act Section 602 (40 CFR 82, Subpt. A, App.A + B).

Additional ecological information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Harmful to aquatic life with long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues

: The product should not be allowed to enter drains, water courses or the soil.
Do not contaminate ponds, waterways or ditches with chemical or used container.
Dispose of in accordance with local regulations.

Contaminated packaging

: Empty remaining contents.
Dispose of as unused product.
Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

Transportation Regulation: 49 CFR (USA):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IMDG (Vessel):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Cargo Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: IATA (Passenger Air):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

Transportation Regulation: TDG (Canada):
NOT REGULATED AS DANGEROUS GOODS OR HAZARDOUS MATERIAL

The product as delivered to the customer conforms to packaging requirements for shipment by road under US Department of Transportation (DOT) regulations. Additional transportation classifications noted above are for reference only, and not a certification or warranty of the suitability of the packaging for shipment under these alternative transport regulations.

SECTION 15. REGULATORY INFORMATION

TSCA list : No substances are subject to a Significant New Use Rule.

No substances are subject to TSCA 12(b) export notification requirements.

EPCRA - Emergency Planning and Community Right-to-Know Act

CERCLA Reportable Quantity

Components	CAS-No.	Component RQ (lbs)	Calculated product RQ (lbs)
xylenes	1330-20-7	100	*

*: Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Germ cell mutagenicity
Reproductive toxicity

SARA 302 : No chemicals in this material are subject to the reporting requirements of SARA Title III, Section 302.

SAFETY DATA SHEET

MISTY ULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

SARA 313

: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop. 65



WARNING: This product can expose you to chemicals including ethylbenzene, which is/are known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

The components of this product are reported in the following inventories:

DSL	All components of this product are on the Canadian DSL
TSCA	On TSCA Inventory

For information on the country notification status for other regions please contact the manufacturer's regulatory group.

Inventory Acronym and Validity Area Legend:

TSCA (USA), DSL (Canada), NDSL (Canada)

SECTION 16. OTHER INFORMATION

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

Further information

NFPA:

HEALTH	1
FLAMMABILITY	1
INSTABILITY	0
SPECIAL HAZARD.	

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme

HMIS III:

HEALTH	1
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,
2 = Moderate, 3 = High
4 = Extreme, * = Chronic

OSHA - GHS Label Information:

Hazard pictograms



Health hazard

Signal word

: **Danger:**

Hazard statements

: May cause genetic defects. Suspected of damaging fertility or the unborn child.

Precautionary statements

:

Prevention: Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response: IF exposed or concerned: Get medical advice/ attention.

Storage: Store locked up.

Disposal: Dispose of contents/container in accordance with local regulation.

Version:	3.1
Revision Date:	10/01/2023
Print Date:	10/05/2023

SAFETY DATA SHEET

MISTYULTRA HIGH TEMP SYNTHETIC BLEND 14OZ 48T

Version 3.1

Revision Date 10/01/2023

Print Date 10/05/2023

We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. Users should make their own investigations to determine the suitability and applicability of the information for their particular purposes.

This SDS has been prepared by the Compliance Services organization supporting this manufacturer, supplier or distributor.