



## SAFETY DATA SHEET MC-236BKA MAKE-UP

According to Appendix D, OSHA Hazard Communication Standard 29 CFR §1910.1200

### 1. Identification

#### Product identifier

Product name MC-236BKA MAKE-UP

Product number MC-236BKA

#### Recommended use of the chemical and restrictions on use

Application Printing Ink Related Material.

#### Details of the supplier of the safety data sheet

Supplier Domino Amjet Inc  
1290 Lakeside Drive  
Gurnee, Illinois 60031  
Tel: +1 847 244 2501  
Fax: +1 847 244 1421  
Email: sds@domino-uk.com

#### Emergency telephone number

Emergency telephone For MEDICAL emergencies call:  
International Poison Control Center, USA  
1-800-228-5635 (24 Hours)  
+1 612-851-8180 (24 hours, International)

For TRANSPORTATION emergencies call:  
CHEMTREC 1-800-424-9300 (US Calls)  
+1 703-527-3887 (International calls)

### 2. Hazard(s) identification

#### Classification of the substance or mixture

Physical hazards Flam. Liq. 2 - H225

Health hazards Eye Irrit. 2A - H319 STOT SE 3 - H336

Environmental hazards Not Classified

#### Label elements

##### Pictogram



Signal word Danger

Hazard statements  
H225 Highly flammable liquid and vapor.  
H319 Causes serious eye irritation.  
H336 May cause drowsiness or dizziness.

## MC-236BKA MAKE-UP

|                          |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Precautionary statements | <p>P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking.</p> <p>P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.</p> <p>P304+P340 If inhaled: Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.</p> <p>P403+P233 Store in a well-ventilated place. Keep container tightly closed.</p> <p>P501 Dispose of contents/ container in accordance with national regulations.</p> |
|--------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

|          |            |
|----------|------------|
| Contains | 2-Butanone |
|----------|------------|

### Other hazards

None known.

### 3. Composition/information on ingredients

#### Mixtures

|                                                                                   |          |
|-----------------------------------------------------------------------------------|----------|
| 2-Butanone<br>CAS number: 78-93-3                                                 | 80-84.9% |
| Classification<br>Flam. Liq. 2 - H225<br>Eye Irrit. 2A - H319<br>STOT SE 3 - H336 |          |
| Ethanol<br>CAS number: 64-17-5                                                    | 10-20%   |
| Classification<br>Flam. Liq. 2 - H225<br>Eye Irrit. 2A - H319                     |          |

The full text for all hazard statements is displayed in Section 16.

### 4. First-aid measures

#### Description of first aid measures

|                            |                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
|----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General information        | Get medical attention. Show this Safety Data Sheet to the medical personnel.                                                                                                                                                                                                                                                                                                                                                                           |
| Inhalation                 | Remove affected person from source of contamination. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing. Maintain an open airway. Loosen tight clothing such as collar, tie or belt. When breathing is difficult, properly trained personnel may assist affected person by administering oxygen. Place unconscious person on their side in the recovery position and ensure breathing can take place. |
| Ingestion                  | IF SWALLOWED: Get medical attention. Rinse mouth thoroughly with water. Do not induce vomiting unless under the direction of medical personnel. Move affected person to fresh air and keep warm and at rest in a position comfortable for breathing.                                                                                                                                                                                                   |
| Skin Contact               | IF ON SKIN: Rinse immediately with plenty of water.                                                                                                                                                                                                                                                                                                                                                                                                    |
| Eye contact                | IF IN EYES: Rinse immediately with plenty of water. Get medical attention if irritation persists after washing.                                                                                                                                                                                                                                                                                                                                        |
| Protection of first aiders | First aid personnel should wear appropriate protective equipment during any rescue.                                                                                                                                                                                                                                                                                                                                                                    |

#### Most important symptoms and effects, both acute and delayed

|                     |                                                                                                                                                                          |
|---------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General information | See Section 11 for additional information on health hazards. The severity of the symptoms described will vary dependent on the concentration and the length of exposure. |
| Inhalation          | A single exposure may cause the following adverse effects: Drowsiness, dizziness, disorientation, vertigo. Headache. Nausea, vomiting.                                   |

## MC-236BKA MAKE-UP

Ingestion                      Gastrointestinal symptoms, including upset stomach. Fumes from the stomach contents may be inhaled, resulting in the same symptoms as inhalation.

Skin contact                      Prolonged contact may cause dryness of the skin.

Eye contact                      Irritating to eyes.

### Indication of immediate medical attention and special treatment needed

Notes for the doctor                      Treat symptomatically.

## 5. Fire-fighting measures

### Extinguishing media

Suitable extinguishing media                      Extinguish with alcohol-resistant foam, carbon dioxide, dry powder or water fog.

Unsuitable extinguishing media                      Do not use water jet as an extinguisher, as this will spread the fire.

### Special hazards arising from the substance or mixture

Specific hazards                      Flammable liquid and vapour. Vapors may be ignited by a spark, a hot surface or an ember. Vapors may form explosive mixtures with air. Containers can burst violently or explode when heated, due to excessive pressure build-up. Take precautionary measures against static discharges.

Hazardous combustion products                      Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Carbon monoxide (CO). Carbon dioxide (CO<sub>2</sub>).

### Advice for firefighters

Protective actions during firefighting                      Avoid breathing fire gases or vapors. Evacuate area. Keep upwind to avoid inhalation of gases, vapors, fumes and smoke. Ventilate closed spaces before entering them. Cool containers exposed to heat with water spray and remove them from the fire area if it can be done without risk. Cool containers exposed to flames with water until well after the fire is out. Control run-off water by containing and keeping it out of sewers and watercourses. If risk of water pollution occurs, notify appropriate authorities.

Special protective equipment for firefighters                      Wear positive-pressure self-contained breathing apparatus (SCBA) and appropriate protective clothing. Standard Firefighter's clothing including helmets, protective boots and gloves will provide a basic level of protection for chemical incidents.

## 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

Personal precautions                      No action shall be taken without appropriate training or involving any personal risk. Keep unnecessary and unprotected personnel away from the spillage. Wear protective clothing as described in Section 8 of this safety data sheet. Follow precautions for safe handling described in this safety data sheet. Wash thoroughly after dealing with a spillage. Ensure procedures and training for emergency decontamination and disposal are in place. Do not touch or walk into spilled material. No smoking, sparks, flames or other sources of ignition near spillage.

### Environmental precautions

Environmental precautions                      Contain spillage with sand, earth or other suitable non-combustible material. Use appropriate containment to avoid environmental contamination.

### Methods and material for containment and cleaning up

Methods for cleaning up                      Wear protective clothing as described in Section 8 of this safety data sheet. Clear up spills immediately and dispose of waste safely. Eliminate all ignition sources if safe to do so. No smoking, sparks, flames or other sources of ignition near spillage. Small Spillages: Wipe up with an absorbent cloth and dispose of waste safely. Large Spillages: Contain and absorb spillage with sand, earth or other non-combustible material. Place waste in labeled, sealed containers. Clean contaminated objects and areas thoroughly, observing environmental regulations. The contaminated absorbent may pose the same hazard as the spilled material. Flush contaminated area with plenty of water. Wash thoroughly after dealing with a spillage. Collect and dispose of spillage as indicated in Section 13.

Reference to other sections                      For personal protection, see Section 8. See Section 11 for additional information on health hazards. See Section 12 for additional information on ecological hazards. For waste disposal, see Section 13.

## MC-236BKA MAKE-UP

### 7. Handling and storage

#### Precautions for safe handling

##### Usage precautions

Flammable/combustible materials. Do not handle until all safety precautions have been read and understood. Wear protective clothing as described in Section 8 of this safety data sheet. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Take precautionary measures against static discharges. Use only non-sparking tools.

##### Advice on general occupational hygiene

Wash promptly if skin becomes contaminated. Take off contaminated clothing and wash before reuse. Do not eat, drink or smoke when using this product.

#### Conditions for safe storage, including any incompatibilities

##### Storage precautions

Eliminate all sources of ignition. Keep away from oxidizing materials, heat and flames. Keep only in the original container. Keep containers upright. Take precautionary measures against static discharges.

##### Storage class

Flammable liquid storage.

#### Specific end uses(s)

##### Specific end use(s)

The identified uses for this product are detailed in Section 1.

### 8. Exposure Controls/personal protection

#### Control parameters

##### Occupational exposure limits

##### 2-Butanone

Long-term exposure limit (8-hour TWA): ACGIH 200 ppm 590 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 300 ppm 885 mg/m<sup>3</sup>

Long-term exposure limit (8-hour TWA): OSHA 200 ppm 590 mg/m<sup>3</sup>

##### Ethanol

Long-term exposure limit (8-hour TWA): OSHA 1000 ppm 1900 mg/m<sup>3</sup>

Short-term exposure limit (15-minute): ACGIH 1000 ppm 1880 mg/m<sup>3</sup>

##### A3

ACGIH = American Conference of Governmental Industrial Hygienists.

OSHA = Occupational Safety and Health Administration.

A3 = Confirmed Animal Carcinogen with Unknown Relevance to Humans.

#### 2-Butanone (CAS: 78-93-3)

Immediate danger to life and health 3000 ppm

#### Ethanol (CAS: 64-17-5)

Immediate danger to life and health 3300 ppm

#### Exposure controls

##### Protective equipment



##### Appropriate engineering controls

As this product contains ingredients with exposure limits, process enclosures, local exhaust ventilation or other engineering controls should be used to keep worker exposure below any statutory or recommended limits, if use generates dust, fumes, gas, vapor or mist. Personal, workplace environment or biological monitoring may be required to determine the effectiveness of the ventilation or other control measures and/or the necessity to use respiratory protective equipment. Ensure control measures are regularly inspected and maintained. The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits.

## MC-236BKA MAKE-UP

|                                 |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |
|---------------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Eye/face protection             | Wear tight-fitting, chemical splash goggles or face shield. Personal protective equipment for eye and face protection should comply with OSHA 1910.133.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |
| Hand protection                 | Chemical-resistant, impervious gloves complying with an approved standard should be worn if a risk assessment indicates skin contact is possible. To protect hands from chemicals, gloves should comply with OSHA 1910.138 and be demonstrated to be impervious to the chemical and resist degradation. Frequent changes are recommended. It is recommended that gloves are made of the following material: Laminate of polyethylene and ethylene vinyl alcohol (PE/EVOH). The selected gloves should have a breakthrough time of at least 8 hours. Polyvinyl alcohol (PVA). The selected gloves should have a breakthrough time of at least 0.75 hours. The most suitable glove should be chosen in consultation with the glove supplier/manufacture, who can provide information about the breakthrough time of the glove material. It should be noted that liquid may penetrate the gloves. |
| Other skin and body protection  | Wear anti-static protective clothing if there is a risk of ignition from static electricity. Wear appropriate clothing to prevent skin contamination.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |
| Hygiene measures                | Provide eyewash station and safety shower. Wash contaminated clothing before reuse. Wash at the end of each work shift and before eating, smoking and using the toilet. When using do not eat, drink or smoke.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |
| Respiratory protection          | If ventilation is inadequate, suitable respiratory protection must be worn. Respiratory protection must be used if the airborne contamination exceeds the recommended occupational exposure limit.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |
| Environmental exposure controls | Keep container tightly sealed when not in use.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |

### 9. Physical and Chemical Properties

#### Information on basic physical and chemical properties

|                                              |                                                                                                                                         |
|----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|
| Appearance                                   | Liquid.                                                                                                                                 |
| Color                                        | Light (or pale). Black.                                                                                                                 |
| Odor                                         | Ketonic.                                                                                                                                |
| Odor threshold                               | Not available.                                                                                                                          |
| pH                                           | Not applicable.                                                                                                                         |
| Melting point                                | -86°C Information given is applicable to the major ingredient.                                                                          |
| Initial boiling point and range              | ~79.6°C @ 1013 hPa Information given is applicable to the major ingredient.                                                             |
| Flash point                                  | ~ -6°C Closed cup.                                                                                                                      |
| Evaporation rate                             | Not available.                                                                                                                          |
| Flammability (solid, gas)                    | Not available.                                                                                                                          |
| Upper/lower flammability or explosive limits | Lower flammable/explosive limit: 1.8 % Upper flammable/explosive limit: 11.5 % Information given is applicable to the major ingredient. |
| Vapor pressure                               | 105 hPa @ 20°C 126 hPa @ 25°C Information given is applicable to the major ingredient.                                                  |
| Vapor density                                | > 1                                                                                                                                     |
| Relative density                             | 0.7980 @ 25°C                                                                                                                           |
| Solubility(ies)                              | 270 g/l water @ 20°C Information given is applicable to the major ingredient. Soluble in the following materials: Organic solvents.     |
| Partition coefficient                        | log Pow: 0.3 Information given is applicable to the major ingredient.                                                                   |
| Auto-ignition temperature                    | 404°C Information given is applicable to the major ingredient.                                                                          |
| Decomposition Temperature                    | Not available.                                                                                                                          |
| Viscosity                                    | 0.94 cP @ 25°C                                                                                                                          |
| Explosive properties                         | Not considered to be explosive.                                                                                                         |
| Oxidizing properties                         | Does not meet the criteria for classification as oxidizing.                                                                             |

## MC-236BKA MAKE-UP

Volatile organic compound      This product contains a maximum VOC content of 100 %. This product contains a maximum VOC content of 0.802 kg/l.

### 10. Stability and reactivity

|                                    |                                                                                                                                                                                                                                                                                                                      |
|------------------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Reactivity                         | See Section 10 (Possibility of hazardous reactions) for further information.                                                                                                                                                                                                                                         |
| Stability                          | Stable at normal ambient temperatures and when used as recommended. Stable under the prescribed storage conditions.                                                                                                                                                                                                  |
| Possibility of hazardous reactions | The following materials may react strongly with the product: Oxidizing agents.                                                                                                                                                                                                                                       |
| Conditions to avoid                | Avoid heat, flames and other sources of ignition. Containers can burst violently or explode when heated, due to excessive pressure build-up. Static electricity and formation of sparks must be prevented. Do not pressurize, cut, weld, drill, grind or otherwise expose containers to heat or sources of ignition. |
| Materials to avoid                 | Oxidizing materials.                                                                                                                                                                                                                                                                                                 |
| Hazardous decomposition products   | Does not decompose when used and stored as recommended. Thermal decomposition or combustion products may include the following substances: Harmful gases or vapors. Carbon dioxide (CO <sub>2</sub> ). Carbon monoxide (CO).                                                                                         |

### 11. Toxicological information

#### Information on toxicological effects

|                                                  |                                                                  |
|--------------------------------------------------|------------------------------------------------------------------|
| Acute toxicity - oral                            |                                                                  |
| Notes (oral LD <sub>50</sub> )                   | Based on available data the classification criteria are not met. |
| Acute toxicity - dermal                          |                                                                  |
| Notes (dermal LD <sub>50</sub> )                 | Based on available data the classification criteria are not met. |
| Acute toxicity - inhalation                      |                                                                  |
| Notes (inhalation LC <sub>50</sub> )             | Based on available data the classification criteria are not met. |
| Skin corrosion/irritation                        |                                                                  |
| Animal data                                      | Repeated exposure may cause skin dryness or cracking.            |
| Serious eye damage/irritation                    |                                                                  |
| Serious eye damage/irritation                    | Causes serious eye irritation.                                   |
| Respiratory sensitization                        |                                                                  |
| Respiratory sensitization                        | Based on available data the classification criteria are not met. |
| Skin sensitization                               |                                                                  |
| Skin sensitization                               | Based on available data the classification criteria are not met. |
| Germ cell mutagenicity                           |                                                                  |
| Genotoxicity - in vitro                          | Based on available data the classification criteria are not met. |
| Carcinogenicity                                  |                                                                  |
| Carcinogenicity                                  | Based on available data the classification criteria are not met. |
| IARC carcinogenicity                             | None of the ingredients are listed or exempt.                    |
| Reproductive toxicity                            |                                                                  |
| Reproductive toxicity - fertility                | Based on available data the classification criteria are not met. |
| Reproductive toxicity - development              | Based on available data the classification criteria are not met. |
| Specific target organ toxicity - single exposure |                                                                  |
| STOT - single exposure                           | STOT SE 3 - H336 May cause drowsiness or dizziness.              |

## MC-236BKA MAKE-UP

Target organs Central nervous system

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information The severity of the symptoms described will vary dependent on the concentration and the length of exposure.

Inhalation A single exposure may cause the following adverse effects: Headache. Nausea, vomiting. Central nervous system depression. Drowsiness, dizziness, disorientation, vertigo. Narcotic effect.

Ingestion No specific symptoms known.

Skin Contact Repeated exposure may cause skin dryness or cracking.

Eye contact Irritating to eyes.

Route of exposure Ingestion Inhalation Skin and/or eye contact

Target Organs Central nervous system

Toxicological information on ingredients.

### 2-Butanone

#### Acute toxicity - oral

Notes (oral LD<sub>50</sub>) LD<sub>50</sub> >2000 mg/kg, Oral, Rat

#### Acute toxicity - dermal

Notes (dermal LD<sub>50</sub>) LD<sub>50</sub> >2000 mg/kg, Dermal, Rabbit

### Ethanol

#### Acute toxicity - oral

Acute toxicity oral (LD<sub>50</sub> mg/kg) 12,400.0

Species Rat

Notes (oral LD<sub>50</sub>) REACH dossier information.

ATE oral (mg/kg) 12,400.0

#### Acute toxicity - dermal

Acute toxicity dermal (LD<sub>50</sub> mg/kg) 17,100.0

Species Rabbit

Notes (dermal LD<sub>50</sub>) REACH dossier information.

ATE dermal (mg/kg) 17,100.0

#### Acute toxicity - inhalation

Acute toxicity inhalation (LC<sub>50</sub> vapours mg/l) 125.0

Species Rat

Notes (inhalation LC<sub>50</sub>) REACH dossier information.

ATE inhalation (vapours mg/l) 125.0

## MC-236BKA MAKE-UP

### 12. Ecological Information

**Ecotoxicity** Not regarded as dangerous for the environment. However, large or frequent spills may have hazardous effects on the environment.

**Toxicity** Based on available data the classification criteria are not met.

Ecological information on ingredients.

#### 2-Butanone

##### Acute aquatic toxicity

|                                        |                                                                                                             |
|----------------------------------------|-------------------------------------------------------------------------------------------------------------|
| Acute toxicity - fish                  | REACH dossier information.<br>LC <sub>50</sub> , 96 hours: 2993 mg/l, Pimephales promelas (Fat-head Minnow) |
| Acute toxicity - aquatic invertebrates | REACH dossier information.<br>EC <sub>50</sub> , 48 hours: 308 mg/l, Daphnia magna                          |
| Acute toxicity - aquatic plants        | REACH dossier information.<br>EC <sub>50</sub> , 72 hours: 1972 mg/l, Selenastrum capricornutum             |

#### Ethanol

##### Acute aquatic toxicity

|                                        |                                                                                                       |
|----------------------------------------|-------------------------------------------------------------------------------------------------------|
| Acute toxicity - fish                  | REACH dossier information.<br>EC <sub>0</sub> , 200 hours: 3900 mg/l, Oryzias latipes (Red killifish) |
| Acute toxicity - aquatic invertebrates | EC <sub>50</sub> , 24 hours: 20803 mg/l, Daphnia magna                                                |
| Acute toxicity - aquatic plants        | NOEC, 7 days: 467 mg/l, Freshwater plants                                                             |
| Acute toxicity - microorganisms        | IC <sub>50</sub> , 3 hours: >1000 mg/l, Activated sludge                                              |
| Acute toxicity - terrestrial           | LC <sub>50</sub> , 48 hours: >1 mg/cm <sup>2</sup> , Eisenia Fetida (Earthworm)                       |

##### Chronic aquatic toxicity

|                                          |                                                                  |
|------------------------------------------|------------------------------------------------------------------|
| Chronic toxicity - fish early life stage | NOEC, 42 hours: 500 mg/l, Brachydanio rerio (Zebra Fish)         |
| Chronic toxicity - aquatic invertebrates | LC <sub>50</sub> , 4 days: 12070 mg/l, Marinewater invertebrates |

##### Persistence and degradability

**Persistence and degradability** The degradability of the product is not known.

##### Bioaccumulative potential

**Bio-Accumulative Potential** No data available on bioaccumulation.

**Partition coefficient** log Pow: 0.3 Information given is applicable to the major ingredient.

Ecological information on ingredients.

#### 2-Butanone

|                       |              |
|-----------------------|--------------|
| Partition coefficient | log Pow: 0.3 |
|-----------------------|--------------|

#### Ethanol

|                       |               |
|-----------------------|---------------|
| Partition coefficient | log Pow: 0.32 |
|-----------------------|---------------|

##### Mobility in soil

**Mobility** No data available.

## MC-236BKA MAKE-UP

### Other adverse effects

Other adverse effects                      None known.

### 13. Disposal considerations

#### Waste treatment methods

|                     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| General information | The generation of waste should be minimized or avoided wherever possible. This material and its container must be disposed of in a safe way. Disposal of this product, process solutions, residues and by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any local authority requirements. When handling waste, the safety precautions applying to handling of the product should be considered. Care should be taken when handling emptied containers that have not been thoroughly cleaned or rinsed out. |
| Disposal methods    | Dispose of waste product or used containers in accordance with local regulations Only store in correctly labeled containers.                                                                                                                                                                                                                                                                                                                                                                                                                                                          |

### 14. Transport information

#### UN Number

|               |        |
|---------------|--------|
| UN No. (TDG)  | 1210   |
| UN No. (IMDG) | 1210   |
| UN No. (ICAO) | 1210   |
| UN No. (DOT)  | UN1210 |

#### UN proper shipping name

|                             |                               |
|-----------------------------|-------------------------------|
| Proper shipping name (TDG)  | PRINTING INK RELATED MATERIAL |
| Proper shipping name (IMDG) | PRINTING INK RELATED MATERIAL |
| Proper shipping name (ICAO) | PRINTING INK RELATED MATERIAL |
| Proper shipping name (DOT)  | PRINTING INK RELATED MATERIAL |

#### Transport hazard class(es)

|                     |   |
|---------------------|---|
| DOT hazard class    | 3 |
| DOT hazard label    | 3 |
| TDG class           | 3 |
| TDG label(s)        | 3 |
| IMDG Class          | 3 |
| ICAO class/division | 3 |

#### Transport labels



#### DOT transport labels



#### Packing group

|                    |    |
|--------------------|----|
| TDG Packing Group  | II |
| IMDG packing group | II |
| ICAO packing group | II |

## MC-236BKA MAKE-UP

DOT packing group II

### Environmental hazards

Environmentally Hazardous Substance  
No.

### Special precautions for user

EmS F-E, S-D

DOT reportable quantity RQ: Methyl ethyl ketone (MEK) (6024.3141 lbs)

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not applicable.

### 15. Regulatory information

#### US Federal Regulations

SARA Section 302 Extremely Hazardous Substances Tier II Threshold Planning Quantities  
None of the ingredients are listed or exempt.

#### CERCLA/Superfund, Hazardous Substances/Reportable Quantities (EPA)

The following ingredients are listed or exempt:

##### *2-Butanone*

Final CERCLA RQ: 5000(2270) pounds (Kilograms)

#### SARA Extremely Hazardous Substances EPCRA Reportable Quantities

None of the ingredients are listed or exempt.

#### SARA 313 Emission Reporting

The following ingredients are listed or exempt:

*reaction mass of: tert-alkyl(C12-C14)ammonium bis[1-[(2-hydroxy-5- nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-) tert-alkyl(C12-C14)ammonium bis[1-[(2- hydroxy-4-nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-) tert-alkyl(C12-C14)ammonium bis[1- [[5-(1,1-dimethylpropyl)-2-hydroxy-3-nitrophenyl]azo]-2-naphthalenolato(2-)]-chromate(1-) tertalkyl(C12-C14)ammonium [[1-[(2-hydroxy-4-nitrophenyl)azo]-2-naphthalenolato(2-)]-[1-[(2-hydroxy-5- nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-) tert-alkyl(C12-C14)ammonium [[1-[[5-(1,1- dimethylpropyl)-2-hydroxy-3-nitrophenyl]azo]-2-naphthalenolato(2-)]-[1-[(2-hydroxy-5- nitrophenyl)azo]-2-naphthalenolato(2-)]-chromate(1-) tert-alkyl(C12-C14)ammonium ((1-(4-nitro-2- oxidophenylazo)-2-naphtholato)(1-(3-nitro-2-oxido-5-(1,1-dimethylpropyl)phenylazo)-2- naphtholato))chromate(1-)*

1.0 %

#### CAA Accidental Release Prevention

None of the ingredients are listed or exempt.

#### FDA - Essential Chemical

None of the ingredients are listed or exempt.

#### FDA - Precursor Chemical

None of the ingredients are listed or exempt.

#### SARA (311/312) Hazard Categories

None of the ingredients are listed or exempt.

#### OSHA Highly Hazardous Chemicals

None of the ingredients are listed or exempt.

#### US State Regulations

##### California Proposition 65 Carcinogens and Reproductive Toxins

None of the ingredients are listed or exempt.

##### California Air Toxics "Hot Spots" (A-I)

The following ingredients are listed or exempt:

## MC-236BKA MAKE-UP

### *2-Butanone*

Present.

### California Air Toxics "Hot Spots" (A-II)

None of the ingredients are listed or exempt.

### California Directors List of Hazardous Substances

The following ingredients are listed or exempt:

#### *2-Butanone*

Present.

#### *Ethanol*

Present.

### Massachusetts "Right To Know" List

The following ingredients are listed or exempt:

#### *2-Butanone*

Present.

#### *Ethanol*

Present.

### Rhode Island "Right To Know" List

The following ingredients are listed or exempt:

#### *2-Butanone*

Present.

#### *Ethanol*

Present.

### Minnesota "Right To Know" List

The following ingredients are listed or exempt:

#### *2-Butanone*

Present.

#### *Ethanol*

Present.

### New Jersey "Right To Know" List

The following ingredients are listed or exempt:

#### *2-Butanone*

Present.

#### *Ethanol*

Present.

### Pennsylvania "Right To Know" List

The following ingredients are listed or exempt:

#### *2-Butanone*

Present.

#### *Ethanol*

Present.

## 16. Other information

Key literature references and sources for data

Source: European Chemicals Agency, <http://echa.europa.eu/> Supplier's information.

Revision comments

DUE TO AN UPDATE OF OUR SDS DATABASE THE VERSION NUMBER OF THIS SDS HAS REVERTED TO V1 AND SUPERSEDES PREVIOUS OLDER VERSIONS

**MC-236BKA MAKE-UP**

|                                      |                                                                                                                           |
|--------------------------------------|---------------------------------------------------------------------------------------------------------------------------|
| Revision date                        | 10/1/2018                                                                                                                 |
| Revision                             | 1                                                                                                                         |
| SDS No.                              | 1684                                                                                                                      |
| Hazard statements in full            | H225 Highly flammable liquid and vapor.<br>H319 Causes serious eye irritation.<br>H336 May cause drowsiness or dizziness. |
| ACA HMIS Health rating.              | Moderate Hazard. (2)                                                                                                      |
| ACA HMIS Flammability rating.        | Ignites easily. (3)                                                                                                       |
| ACA HMIS Physical hazard rating.     | Normally stable. (0)                                                                                                      |
| ACA HMIS Personal protection rating. | B                                                                                                                         |

This information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process. Such information is, to the best of the company's knowledge and belief, accurate and reliable as of the date indicated. However, no warranty, guarantee or representation is made to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability of such information for his own particular use.