

# SAFETY DATA SHEET

1. Identification

**Product identifier** Matheson Select® Anti-Spatter and Nozzle Shield - 1 lb 8 oz

Other means of identification

No. MSG-620-24OZ (Item# 1008289) **Product Code** 

Recommended use Protects from spatter build-up

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section Recommended restrictions

3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

Manufacturer/Importer/Supplier/Distributor information

Manufactured or sold by:

Company name CRC Industries, Inc.

**Address** 885 Louis Dr.

Warminster, PA 18974 US

**Telephone** 

**General Information** 215-674-4300 **Technical Assistance** 800-521-3168 **Customer Service** 800-272-4620 24-Hour Emergency

(CHEMTREC)

800-424-9300 (US)

Website www.crcindustries.com

# 2. Hazard(s) identification

**Physical hazards** Gases under pressure Compressed gas

**Health hazards** Acute toxicity, oral Category 4

> Skin corrosion/irritation Category 2 Serious eye damage/eye irritation Category 2A Category 1B Carcinogenicity

Specific target organ toxicity, single exposure Category 3 narcotic effects

Specific target organ toxicity, repeated Category 2

exposure

**Environmental hazards** Not classified. Not classified. **OSHA** defined hazards

Label elements



Signal word

Contains gas under pressure; may explode if heated. Harmful if swallowed. Causes skin irritation. **Hazard statement** 

Causes serious eye irritation. May cause drowsiness or dizziness. May cause cancer. May cause

damage to organs through prolonged or repeated exposure.

**Precautionary statement** 

Prevention

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not puncture or incinerate container. Do not expose to heat or store at temperatures above 49 °C/120 °F. Do not breathe mist or vapor. Use with adequate ventilation. Open doors and windows or use other means to ensure a fresh air supply during use and while product is drying. If you experience any symptoms listed on this label, increase ventilation or leave the area. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.

Response If swallowed: Call a poison center/doctor if you feel unwell. Rinse mouth. If on skin: Wash with

plenty of water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash before reuse. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell. If exposed or concerned: Get medical

advice/attention.

Storage Store locked up. Protect from sunlight. Store in a well-ventilated place. Exposure to high

temperature may cause can to burst.

**Disposal** Dispose of contents/container in accordance with local/regional/national regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

Supplemental information When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal

corrosive gases such as hydrogen chloride and possibly phosgene.

# 3. Composition/information on ingredients

### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
methylene chloride		75-09-2	90 - 100
carbon dioxide		124-38-9	5 - 10

Specific chemical identity and/or percentage of composition has been withheld as a trade secret.

### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTER or doctor/physician if you feel unwell.

**Skin contact** Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

**Ingestion** Rinse mouth. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs.

Get medical advice/attention if you feel unwell.

Most important symptoms/effects, acute and

delayed

Indication of immediate medical attention and special treatment needed

General information

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation.

Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. Prolonged exposure may cause chronic effects.

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

under observation. Symptoms may be delayed.

IF exposed or concerned: Get medical advice/attention. Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data

sheet to the doctor in attendance.

# 5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing

media

Specific hazards arising from the chemical

Special protective equipment and precautions for firefighters

Fire-fighting equipment/instructions General fire hazards

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Pressurized container may rupture when exposed to heat or flame. During fire, gases hazardous to health may be formed. When exposed to extreme heat or hot surfaces, vapors may decompose to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene.

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

In case of fire: Stop leak if safe to do so. Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapor pressure build up.

Contents under pressure. Pressurized container may rupture when exposed to heat or flame.

# 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Many gases are heavier than air and will spread along ground and collect in low or confined areas (sewers, basements, tanks). Wear appropriate protective equipment and clothing during clean-up. Do not breathe mist or vapor. Emergency personnel need self-contained breathing equipment. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil, etc.) away from spilled material. Stop the flow of material, if this is without risk. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

# Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. Use caution around energized equipment. The metal container will conduct electricity if it contacts a live source. This may result in injury to the user from electrical shock and/or flash fire. Do not breathe mist or vapor. Do not taste or swallow. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices. For product usage instructions, see the product label.

# Conditions for safe storage, including any incompatibilities

Level 1 Aerosol.

Contents under pressure. Do not expose to heat or store at temperatures above 120 °F/49 °C as can may burst. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. Store in a well-ventilated place. Stored containers should be periodically checked for general condition and leakage. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

# Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

# US. OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

# US. NIOSH: Pocket Guide to Chemical Hazards Value Components Type Value carbon dioxide (CAS 124-38-9) STEL 54000 mg/m3 30000 ppm TWA 9000 mg/m3

### **Biological limit values**

Components	Value	Determinant	Specimen	Sampling Time	
methylene chloride (CAS 75-09-2)	0.3 mg/l	Dichlorometha ne	Urine	*	

<sup>\* -</sup> For sampling details, please see the source document.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

5000 ppm

### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear protective gloves such as: Polyvinyl alcohol (PVA). Viton/butyl.

Other Wear appropriate chemical resistant clothing.

**Respiratory protection** If engineering controls are not feasible or if exposure exceeds the applicable exposure limits, use a

NIOSH-approved cartridge respirator with an organic vapor cartridge. Use a self-contained breathing apparatus in confined spaces and for emergencies. Air monitoring is needed to

determine actual employee exposure levels.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Observe any medical surveillance requirements. When using do not smoke. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

# 9. Physical and chemical properties

**Appearance** 

Physical state Liquid.
Form Aerosol.
Color Colorless.
Odor Ether-like.
Odor threshold Not available.
pH Not available.

Melting point/freezing point -139 °F (-95 °C) estimated Initial boiling point and boiling 104 °F (40 °C) estimated

range

Flash point None.

Evaporation rate Fast.

Flammability (solid, gas) Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower 15.5 % estimated

(%)

Flammability limit - upper 60

(%)

66.4 % estimated

Vapor pressure 4517.2 hPa estimated

Vapor density > 1 (air = 1)

Relative density 1.33 estimated

Solubility(ies)

Solubility (water) Negligible.

Partition coefficient Not available.

(n-octanol/water)

**Auto-ignition temperature** 1033 °F (556.1 °C) estimated

Decomposition temperature Not available.

Viscosity Not available.

Percent volatile 90.1 % estimated

# 10. Stability and reactivity

**Reactivity**The product is stable and non-reactive under normal conditions of use, storage and transport.

**Chemical stability** Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Heat, flames and sparks. When exposed to extreme heat or hot surfaces, vapors may decompose

to harmful or fatal corrosive gases such as hydrogen chloride and possibly phosgene. Contact with

incompatible materials. Strong oxidizing agents.

Incompatible materials

**Hazardous decomposition** 

products

Carbon oxides. Hydrogen chloride. Phosgene.

# 11. Toxicological information

### Information on likely routes of exposure

Inhalation May cause damage to organs through prolonged or repeated exposure by inhalation. May cause

drowsiness and dizziness. Headache. Nausea, vomiting.

**Skin contact** Causes skin irritation.

**Eye contact** Causes serious eye irritation.

**Ingestion** Harmful if swallowed.

Symptoms related to the physical, chemical and toxicological characteristics

May cause drowsiness and dizziness. Headache. Nausea, vomiting. Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May

cause redness and pain.

# Information on toxicological effects

Acute toxicity Harmful if swallowed.

Components Species Test Results

methylene chloride (CAS 75-09-2)

Acute Dermal

LD50 Rabbit > 2000 mg/kg

Inhalation

LC50 Rat 52 mg/l, 6 Hours

**Skin corrosion/irritation** Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

# Respiratory or skin sensitization

**Respiratory sensitization** Not a respiratory sensitizer.

**Skin sensitization** This product is not expected to cause skin sensitization.

**Germ cell mutagenicity**No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity May cause cancer.

# IARC Monographs. Overall Evaluation of Carcinogenicity

methylene chloride (CAS 75-09-2)

2A Probably carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

methylene chloride (CAS 75-09-2) Cancer

# US. National Toxicology Program (NTP) Report on Carcinogens

methylene chloride (CAS 75-09-2)

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause drowsiness and dizziness.

Specific target organ toxicity -

repeated exposure

May cause damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** May cause damage to organs through prolonged or repeated exposure. Prolonged inhalation may

be harmful. Prolonged exposure may cause chronic effects.

# 12. Ecological information

**Ecotoxicity** The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Components Species Test Results

methylene chloride (CAS 75-09-2)

Aquatic

Crustacea EC50 Water flea (Daphnia magna) 1250 mg/l, 48 hours

Fish LC50 Fathead minnow (Pimephales promelas) 140.8 - 277.8 mg/l, 96 hours

Persistence and degradability

No data is available on the degradability of any ingredients in the mixture.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

methylene chloride 1.25

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

# 13. Disposal considerations

**Disposal instructions**This material and its container must be disposed of as hazardous waste. Collect and reclaim or

U080

dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not

puncture, incinerate or crush. Dispose in accordance with all applicable regulations.

Hazardous waste code F002: Waste methylene chloride - Spent halogenated solvent

**US RCRA Hazardous Waste U List: Reference** 

methylene chloride (CAS 75-09-2)

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

UN number UN1950

UN proper shipping name Aerosols, poison, Limited Quantity

Transport hazard class(es)

Class 2.2
Subsidiary risk 6.1(PGIII)
Label(s) 2.2, 6.1
Packing group Not applicable.

Special precautions for user Forbidden from transportation by air.

Packaging exceptions 306
Packaging non bulk None
Packaging bulk None

**IATA** 

UN number UN1950

**UN proper shipping name** Aerosols, non-flame

Transport hazard class(es)

Aerosols, non-flammable, containing substances in Division 6.1, Packing Group III

Class 2.2 Subsidiary risk 6.1 **Packing group** Not applicable.

**ERG Code** 2P

Special precautions for user Not available.

Other information

Passenger and cargo

aircraft

Allowed with restrictions.

Cargo aircraft only

Allowed with restrictions.

**IMDG** 

UN1950 **UN** number **AEROSOLS UN proper shipping name** 

Transport hazard class(es)

Class 2.2 Subsidiary risk 6.1


Packing group Not applicable.

**Environmental hazards** 

Marine pollutant No.

Not available. **EmS** Special precautions for user Not available.

### DOT



IATA; IMDG



# 15. Regulatory information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

This chemical/product is not and cannot be distributed in commerce (as defined in TSCA section 3(5)) or processed (as defined in TSCA section 3(13)) for consumer paint or coating removal.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

methylene chloride (CAS 75-09-2) 0.1 % Annual Export Notification required.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

methylene chloride (CAS 75-09-2) Cancer

Heart

Central nervous system

Liver

Skin irritation Eye irritation

US EPCRA (SARA Title III) Section 313 - Toxic Chemical: Listed substance

methylene chloride (CAS 75-09-2)

# **CERCLA Hazardous Substance List (40 CFR 302.4)**

methylene chloride (CAS 75-09-2)

# **CERCLA Hazardous Substances: Reportable quantity**

methylene chloride (CAS 75-09-2)

1000 LBS

Spills or releases resulting in the loss of any ingredient at or above its RQ require immediate notification to the National Response Center (800-424-8802) and to your Local Emergency Planning Committee.

# Other federal regulations

### Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

methylene chloride (CAS 75-09-2)

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

Food and Drug

Administration (FDA)

Not regulated.

# Superfund Amendments and Reauthorization Act of 1986 (SARA)

Classified hazard

Gas under pressure

categories

Acute toxicity (any route of exposure)

Skin corrosion or irritation

Serious eye damage or eye irritation

Carcinogenicity

Specific target organ toxicity (single or repeated exposure)

# SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Yes

chemical

### SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
methylene chloride	75-09-2	90 - 100	

# **US** state regulations

# US. New Jersey Worker and Community Right-to-Know Act

carbon dioxide (CAS 124-38-9) methylene chloride (CAS 75-09-2)

# **US. Massachusetts RTK - Substance List**

carbon dioxide (CAS 124-38-9) methylene chloride (CAS 75-09-2)

# US. Pennsylvania Worker and Community Right-to-Know Law

carbon dioxide (CAS 124-38-9) methylene chloride (CAS 75-09-2)

### **US. Rhode Island RTK**

carbon dioxide (CAS 124-38-9) methylene chloride (CAS 75-09-2)

# **California Proposition 65**



**WARNING:** Cancer - www.P65Warnings.ca.gov

### California Proposition 65 - CRT: Listed date/Carcinogenic substance

methylene chloride (CAS 75-09-2) Listed: April 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

methylene chloride (CAS 75-09-2)

# Volatile organic compounds (VOC) regulations

**EPA** 

VOC content (40 CFR

51.100(s))

**Consumer products** 

Not regulated

(40 CFR 59, Subpt. C)

Material name: Matheson Select® Anti-Spatter and Nozzle Shield - 1 lb 8 oz No. MSG-620-24OZ (Item# 1008289) Version #: 01 Issue date: 07-01-2019 State

Consumer products Not regulated

VOC content (CA) 0 % VOC content (OTC) 0 %

### International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical	Yes

Substances (EINECS)

EuropeEuropean List of Notified Chemical Substances (ELINCS)NoJapanInventory of Existing and New Chemical Substances (ENCS)NoKoreaExisting Chemicals List (ECL)YesNew ZealandNew Zealand InventoryYesPhilippinesPhilippine Inventory of Chemicals and Chemical SubstancesYes

(PICCS)

Taiwan Chemical Substance Inventory (TCSI)

United States & Puerto Rico Toxic Substances Control Act (TSCA) Inventory

Yes

# 16. Other information, including date of preparation or last revision

Issue date07-01-2019Prepared byDustin Kern

Version # 01

**Disclaimer**The information contained in this document applies to this specific material as supplied. It may not

be valid for this material if it is used in combination with any other materials. This information is accurate to the best of CRC's knowledge or obtained from sources believed by CRC to be accurate. Before using any product, read all warnings and directions on the label. For further clarification of any information contained on this (M)SDS consult your supervisor, a health & safety

professional, or CRC Industries, Inc..

**Revision information** Hazard(s) identification: Response

Transport Information: Material Transportation Information

Material name: Matheson Select® Anti-Spatter and Nozzle Shield - 1 lb 8 oz No. MSG-620-24OZ (Item# 1008289) Version #: 01 Issue date: 07-01-2019

<sup>\*</sup>A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s) A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).