

# Safety Data Sheet



Revision Number: 006.1

Issue date: 03/23/2018

## 1. PRODUCT AND COMPANY IDENTIFICATION

|                            |   |                     |        |
|----------------------------|---|---------------------|--------|
| <b>Product name:</b>       | LOCTITE LB 8150 SV A/S known as<br>Silver Grade Anti-Seize Lubric   | <b>IDH number:</b>  | 235005 |
| <b>Product type:</b>       | Lubricant   | <b>Item number:</b> | 76764  |
| <b>Restriction of Use:</b> | None identified   | <b>Region:</b>      | Canada |
| <b>Company address:</b>    | <b>Contact information:</b><br>Telephone: +1 (905) 814-6511<br>Henkel Canada Corporation<br>Meadowpine Boulevard 2515<br>Mississauga, Ontario L5N 6C3 |                     |        |

## 2. HAZARDS IDENTIFICATION

### EMERGENCY OVERVIEW

**DANGER:** CAUSES SEVERE SKIN BURNS AND EYE DAMAGE.

| HAZARD CLASS       | HAZARD CATEGORY |
|--------------------|-----------------|
| SKIN CORROSION     | 1C              |
| SERIOUS EYE DAMAGE | 1               |

### PICTOGRAM(S)



### Precautionary Statements

|                    |  |
|--------------------|--|
| <b>Prevention:</b> | Wash affected area thoroughly after handling. Wear protective gloves, clothing, eye and face protection.   |
| <b>Response:</b>   | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Immediately call a POISON CENTER or physician. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Wash contaminated clothing before reuse. |
| <b>Storage:</b>    | Store locked up.   |
| <b>Disposal:</b>   | Dispose of contents and/or container according to Federal, State/Provincial and local governmental regulations.  |

Classification complies with Canadian Hazardous Products Regulations (WHMIS 2015) and is consistent with the provision of the United Nations Globally Harmonized System of Classification and Labeling of Chemicals (GHS).

See Section 11 for additional toxicological information.

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

| Hazardous Component(s)                                 | CAS Number | Weight %* |
|--|------------|-----------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 64742-52-5 | 30 - 40   |
| Graphite   | 7782-42-5  | 20 - 30   |
| Calcium oxide  | 1305-78-8  | 10 - 20   |

IDH number: 235005

Product name: LOCTITE LB 8150 SV A/S known as Silver Grade Anti-Seize Lubric

|  |            |         |
|--|------------|---------|
| Aluminum not powder, dust or fume            | 7429-90-5  | 5 - 10  |
| Distillates (petroleum), straight-run middle | 64741-44-2 | 1 - 5   |
| Quartz (SiO <sub>2</sub> ), <1% respirable   | 14808-60-7 | 0.1 - 1 |

\* Exact percentages may vary or are trade secret. Concentration range is provided to assist users in providing appropriate protections.

#### 4. FIRST AID MEASURES

|                      |   |
|----------------------|---|
| <b>Inhalation:</b>   | Move to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.                                      |
| <b>Skin contact:</b> | Remove contaminated clothing and footwear. Immediately flush skin with plenty of water (using soap, if available). Get medical attention. Wash clothing before reuse. |
| <b>Eye contact:</b>  | Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention.   |
| <b>Ingestion:</b>    | Do not induce vomiting. Never give anything by mouth to an unconscious person. Get immediate medical attention.   |
| <b>Symptoms:</b>     | See Section 11.   |

#### 5. FIRE FIGHTING MEASURES

|   |  |
|---|--|
| <b>Extinguishing media:</b>               | Foam, dry chemical or carbon dioxide.  |
| <b>Special firefighting procedures:</b>   | Wear self-contained breathing apparatus and full protective clothing, such as turn-out gear. In case of fire, keep containers cool with water spray. |
| <b>Unusual fire or explosion hazards:</b> | None   |
| <b>Hazardous combustion products:</b>     | Oxides of carbon. Toxic and irritating vapors.   |

#### 6. ACCIDENTAL RELEASE MEASURES

Use personal protection recommended in Section 8, isolate the hazard area and deny entry to unnecessary and unprotected personnel.

|                                   |  |
|-----------------------------------|--|
| <b>Environmental precautions:</b> | Do not allow product to enter sewer or waterways.  |
| <b>Clean-up methods:</b>          | Refer to Section 8 "Exposure Controls / Personal Protection" prior to clean up.<br>For small spills wipe up with paper towel and place in container for disposal.<br>For large spills absorb onto inert absorbent material and place in sealed container for disposal. |

#### 7. HANDLING AND STORAGE

|                  |   |
|------------------|---|
| <b>Handling:</b> | Use only with adequate ventilation. Prevent contact with eyes, skin and clothing. Do not breathe vapor and mist. Wash thoroughly after handling. Keep container closed. |
| <b>Storage:</b>  | Keep in a cool, well ventilated area.   |

**Shelf Life Statement:** Not available.

#### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Employers should complete an assessment of all workplaces to determine the need for, and selection of, proper exposure controls and protective equipment for each task performed.

| Hazardous Component(s)                                 | ACGIH TLV                               | OSHA PEL  | AIHA WEEL | OTHER |
|--|---|---|-----------|-------|
| Distillates (petroleum), hydrotreated heavy naphthenic | 5 mg/m3 TWA<br>Inhalable fraction.      | 5 mg/m3 TWA mist<br>500 ppm (2,000 mg/m3) PEL<br>5 mg/m3 PEL Mist.  | None      | None  |
| Graphite   | 2 mg/m3 TWA<br>Respirable fraction.     | 5 mg/m3 PEL<br>Respirable fraction.<br>15 mg/m3 PEL<br>Total dust.<br>15 MPPCF TWA  | None      | None  |
| Calcium oxide  | 2 mg/m3 TWA                             | 5 mg/m3 PEL   | None      | None  |
| Aluminum not powder, dust or fume                      | None                                    | 5 mg/m3 PEL (as Al) Respirable fraction.<br>15 MPPCF TWA<br>Respirable fraction.<br>50 MPPCF TWA<br>Total dust.<br>5 mg/m3 TWA<br>Respirable fraction.<br>15 mg/m3 TWA<br>Total dust.                             | None      | None  |
| Distillates (petroleum), straight-run middle           | 5 mg/m3 TWA mist                        | 5 mg/m3 TWA mist  | None      | None  |
| Quartz (SiO <sub>2</sub> ), <1% respirable             | 0.025 mg/m3 TWA<br>Respirable fraction. | 2.4 MPPCF TWA<br>Respirable.<br>0.1 mg/m3 TWA<br>Respirable.<br>0.05 mg/m3 TWA<br>(Respirable dust.)<br>(Respirable dust.)<br>0.025 mg/m3<br>OSHA_ACT<br>(Respirable dust.)<br>0.05 mg/m3 PEL<br>Respirable dust. | None      | None  |

**Engineering controls:**

Provide adequate local exhaust ventilation to maintain worker exposure below exposure limits.

**Respiratory protection:**

Use NIOSH approved respirator if there is potential to exceed exposure limit(s).

**Eye/face protection:**

Safety goggles or safety glasses with side shields. Full face protection should be used if the potential for splashing or spraying of product exists. Safety showers and eye wash stations should be available.

**Skin protection:**

Use impermeable gloves and protective clothing as necessary to prevent skin contact.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

|                                     |                      |
|-------------------------------------|----------------------|
| Physical state:                     | Paste                |
| Color:                              | Silver               |
| Odor:                               | Hydrocarbon-like     |
| Odor threshold:                     | Not available.       |
| pH:                                 | Not applicable       |
| Vapor pressure:                     | Not available.       |
| Boiling point/range:                | Not available.       |
| Melting point/ range:               | Not available.       |
| Specific gravity:                   | 1.25                 |
| Vapor density:                      | Not available.       |
| Flash point:                        | > 93 °C (> 199.4 °F) |
| Flammable/Explosive limits - lower: | Not available.       |
| Flammable/Explosive limits - upper: | Not available.       |
| Autoignition temperature:           | Not determined       |

|  |                |
|--|----------------|
| Flammability:                            | Not applicable |
| Evaporation rate:                        | Not available. |
| Solubility in water:                     | Insoluble      |
| Partition coefficient (n-octanol/water): | Not available. |
| VOC content:                             | < 3 %          |
| Viscosity:                               | Not available. |
| Decomposition temperature:               | Not available. |

## 10. STABILITY AND REACTIVITY

|                                   |   |
|-----------------------------------|---|
| Stability:                        | Stable under normal conditions of storage and use.                |
| Hazardous reactions:              | None under normal processing.                                     |
| Hazardous decomposition products: | Oxides of carbon. Irritating organic vapours.                     |
| Incompatible materials:           | Strong oxidizing agents. Acids. Water. Alkalis.                   |
| Reactivity:                       | Not available.  |
| Conditions to avoid:              | Keep away from heat, ignition sources and incompatible materials. |

## 11. TOXICOLOGICAL INFORMATION

Relevant routes of exposure: Skin, Inhalation, Eyes, Ingestion

### Potential Health Effects/Symptoms

|               |  |
|---------------|--|
| Inhalation:   | May cause respiratory tract irritation. Abrasion of cured material such as by sanding or grinding could release respirable particles of silica quartz, a cancer hazard by inhalation. Normal use of this product causes no such release. |
| Skin contact: | Corrosive to the skin. Contact with the skin or mucous membranes may cause severe irritation and burns.  |
| Eye contact:  | Causes serious eye damage.   |
| Ingestion:    | Not expected under normal conditions of use. May cause gastrointestinal tract irritation if swallowed.   |

| Hazardous Component(s)                                 | LD50s and LC50s | Immediate and Delayed Health Effects                  |
|--|-----------------|---|
| Distillates (petroleum), hydrotreated heavy naphthenic | None            | Irritant  |
| Graphite   | None            | Lung  |
| Calcium oxide  | None            | Irritant, Corrosive, Eyes                             |
| Aluminum not powder, dust or fume                      | None            | Central nervous system, Irritant, Lung                |
| Distillates (petroleum), straight-run middle           | None            | Irritant  |
| Quartz (SiO <sub>2</sub> ), <1% respirable             | None            | Immune system, Lung, Some evidence of carcinogenicity |

| Hazardous Component(s)                                 | NTP Carcinogen                | IARC Carcinogen | OSHA Carcinogen (Specifically Regulated) |
|--|-------------------------------|-----------------|--|
| Distillates (petroleum), hydrotreated heavy naphthenic | No                            | No              | No                                       |
| Graphite   | No                            | No              | No                                       |
| Calcium oxide  | No                            | No              | No                                       |
| Aluminum not powder, dust or fume                      | No                            | No              | No                                       |
| Distillates (petroleum), straight-run middle           | No                            | No              | No                                       |
| Quartz (SiO <sub>2</sub> ), <1% respirable             | Known To Be Human Carcinogen. | Group 1         | Yes                                      |

## 12. ECOLOGICAL INFORMATION

Ecological information: Not available.

## 13. DISPOSAL CONSIDERATIONS

Information provided is for unused product only.

Recommended method of disposal: Follow all local, state, federal and provincial regulations for disposal.

## 14. TRANSPORT INFORMATION

The transport information provided in this section only applies to the material/formulation itself, and is not specific to any package/configuration.

### Canada Transportation of Dangerous Goods - Ground

|                           |               |
|---------------------------|---------------|
| Proper shipping name:     | Not regulated |
| Hazard class or division: | None          |
| Identification number:    | None          |
| Packing group:            | None          |

### International Air Transportation (ICAO/IATA)

|                           |  |
|---------------------------|--|
| Proper shipping name:     | Calcium oxide  |
| Hazard class or division: | 8  |
| Identification number:    | UN 1910  |
| Packing group:            | III  |
| Additional information:   | No dangerous good according to ADR/RID/ADN. Carriage in accordance with 1.1.4.2.1 ADR/RID/ADN. |

### Water Transportation (IMO/IMDG)

|                           |               |
|---------------------------|---------------|
| Proper shipping name:     | Not regulated |
| Hazard class or division: | None          |
| Identification number:    | None          |
| Packing group:            | None          |

## 15. REGULATORY INFORMATION

### Canada Regulatory Information

CEPA DSL/NDL Status: All components are listed on or are exempt from listing on the Canadian Domestic Substances List.

### United States Regulatory Information

TSCA 8 (b) Inventory Status: All components are listed or are exempt from listing on the Toxic Substances Control Act Inventory.

## 16. OTHER INFORMATION

This safety data sheet contains changes from the previous version in sections: 8

Prepared by: Product Safety and Regulatory Affairs

Issue date: 03/23/2018

**DISCLAIMER:** The data contained herein are furnished for information only and are believed to be reliable. However, Henkel Corporation and its affiliates ("Henkel") does not assume responsibility for any results obtained by persons over whose methods Henkel has no control. It is the user's responsibility to determine the suitability of Henkel's products or any production methods mentioned herein for a particular purpose, and to adopt such precautions as may be advisable for the protection of property and persons against any hazards that may be involved in the handling and use of any Henkel's products. In light of the foregoing, Henkel specifically disclaims all warranties, express or implied, including warranties of merchantability and fitness for a particular purpose, arising from sale or use of Henkel's products. Henkel further disclaims any liability for consequential or incidental damages of any kind, including lost profits.